

PHILIPS

Fortimo

LED

Fortimo LED Strip 5ft MF
8xx HV6



Datasheet

The Fortimo LED Strip is a uniquely wide portfolio which can be used in all kind of linear indoor luminaire types. Its form factor makes it easy to design-in and handle in production as it complies to Zhaga standards. Due to the availability from 0.25ft up to 5ft lengths only one product family is needed to cover a wide range of needs.

Key features and benefits

- Typical module efficiency of 186 Lm/W (at 4000K CRI80)
- CRI90 High Efficiency typical performance of 174 Lm/W (at 4000K CRI90)
- Long life-time: >72,000 hours
- Excellent color consistency of 3 SDCM
- Two lumen packages per length available: LF (650 lm/ft) and MF (1100 lm/ft)
- Wide range of CCTs available: 2700K, 3000K, 3500K, 4000K, 5000K and 6500K
- Available in High Voltage (HV) and Low Voltage (LV)
- Options in front connector (FC) or back connector (BC)
- Small LED module width of only 20mm
- Available lengths: 0.25ft / 0.5ft / 1ft / 2ft / 4ft (1120mm) / 4ft extended (1150mm) / 5ft (1400mm) / 5ft extended 1450mm)
- Wide temperature (Tc) range -40°C to +80°C
- Five year system warranty

March 2023



Ordering data

Commercial product name	EOC	12NC	EPREL registration #	Box quantity
Fortimo LED Strip 5ft MF 830 FC HV6	8719514 489929 00	9290 029 48706	1413473	110
Fortimo LED Strip 5ft MF 830 BC HV6	8719514 490048 00	9290 029 49306	1413360	110
Fortimo LED Strip 5ft MF 840 FC HV6	8719514 489943 00	9290 029 48806	1413474	110
Fortimo LED Strip 5ft MF 840 BC HV6	8719514 490062 00	9290 029 49406	1413361	110
Fortimo LED Strip 5ft MF 865 FC HV6	8719514 489967 00	9290 029 48906	1413475	110

Drive currents

Parameter	Nominal*	Life**	Max***	Unit
Fortimo LED Strip 5ft MF 8xx HV6	267	720	720	mA

Module temperatures

Parameter	Nominal*	Life**	Max***	Unit
T _c (case temperature at T _c point)	45	75	85	°C

* Nominal value at which typical performance is specified

** Value at which life time is specified

*** Maximum value for safe operation, do not operate above this value

Optical characteristics - table per color (CCT)

Fortimo LED Strip 5ft MF 830 FC HV6


Fortimo LED Strip 5ft MF 830 BC HV6

Parameter	Min	Typ	Max	Unit
Luminous flux	5020	5180	5520	lm
Efficacy	167	176	198	lm/W
Correlated color temperature (CCT)		3000		K
Color coordinates (CIEx, CIEy)		(0.433, 0.400)		-
Color consistency			3	SDCM
CRI	80			
R9	0			
Photometric code		830/339		
Photobiological safety			RG1 unlimited	



Measurement precision $\pm 5\%$ for the flux data and $\pm 6\%$ for the efficacy data. Measurement precision for color coordinates ± 0.005 . Measurement precision for CRI ± 1.5 .

Operation point	830	lm	lm/W
80% I-nom 214mA	Tc 25 °C	4305	183
	Tc-nom 45 °C	4198	180
	Tc-max 85 °C	3944	171
I-nom 267mA	Tc 25 °C	5312	179
	Tc-nom 45 °C	5180	176
	Tc-max 85 °C	4866	167
I-max 720mA	Tc 25 °C	13185	154
	Tc-nom 45 °C	12851	151
	Tc-max 85 °C	12054	144



Fortimo LED Strip 5ft MF 840 FC HV6


Fortimo LED Strip 5ft MF 840 BC HV6

Parameter	Min	Typ	Max	Unit
Luminous flux	5340	5500	6050	lm
Efficacy	178	186	217	lm/W
Correlated color temperature (CCT)		4000		K
Color coordinates (CIEx, CIEy)		(0.381, 0.377)		-
Color consistency			3	SDCM
CRI	80			
R9	0			
Photometric code		840/339		
Photobiological safety			RG1 unlimited	




Measurement precision $\pm 5\%$ for the flux data and $\pm 6\%$ for the efficacy data. Measurement precision for color coordinates ± 0.005 . Measurement precision for CRI ± 1.5 .

Operation point	840	lm	lm/W
80% I-nom 214mA	Tc 25 °C	4573	194
	Tc-nom 45 °C	4454	190
	Tc-max 85 °C	4180	181
I-nom 267mA	Tc 25 °C	5647	190
	Tc-nom 45 °C	5500	186
	Tc-max 85 °C	5162	177
I-max 720mA	Tc 25 °C	14081	164
	Tc-nom 45 °C	13708	161
	Tc-max 85 °C	12848	153




Fortimo LED Strip 5ft MF 865 FC HV6

Parameter	Min	Typ	Max	Unit
Luminous flux	5240	5414	5890	lm
Efficacy	174	183	211	lm/W
Correlated color temperature (CCT)		6500		K
Color coordinates (CIEx, CIEy)		(0.310, 0.324)		-
Color consistency			3	SDCM
CRI	80			
R9	0			
Photometric code		865/339		
Photobiological safety			RG1 unlimited	

Measurement precision ± 5% for the flux data and ± 6% for the efficacy data. Measurement precision for color coordinates ± 0.005. Measurement precision for CRI ± 1.5.

Operation point	865	lm	lm/W
80% I-nom 214mA	Tc 25 °C	4486	190
	Tc-nom 45 °C	4379	187
	Tc-max 85 °C	4111	178
I-nom 267mA	Tc 25 °C	5546	186
	Tc-nom 45 °C	5414	183
	Tc-max 85 °C	5082	175
I-max 720mA	Tc 25 °C	13930	163
	Tc-nom 45 °C	13590	160
	Tc-max 85 °C	12734	152



Electrical characteristics


Parameter	Min	Typ	Max	Unit
Forward voltage	104.4	110.5	112.5	V
Power consumption	27.9	29.5	30.0	W = kWh/1000h
Number of modules in series per chain			2	
Number of modules in parallel			4	

Measurement precision for Vf +/- 3%. Measurement precision for power +/- 3.3%

Tuning information


Flux and efficacy versus current (at Tc nominal)

I [mA]	Flux [%]	Efficacy [%]
720	248	86
494	177	92
267	100	100
214	81	102
134	52	106



Flux and efficacy versus temperature at Tc (at I nominal)

Tc [°C]	Flux [%]	Efficacy [%]
85	94	95
45	100	100
25	103	102
0	105	104




Lumen maintenance

Operation point	Lumen maintenance x 1000 hours	L70			L80			L90		
		B50	B20	B10	B50	B20	B10	B50	B20	B10
80% Inom=214mA	Tc=25°C	>72	>72	>72	>72	>72	>72	>68	>68	>68
	Tc_nom=45°C	>72	>72	>72	>72	>72	>72	>68	68	67
	Tc_life=75°C	>72	>72	>72	>72	>72	>72	47	46	46
Inom=267mA	Tc=25°C	>72	>72	>72	>72	>72	>72	>68	>68	>68
	Tc_nom=45°C	>72	>72	>72	>72	>72	>72	>68	68	67
	Tc_life=75°C	>72	>72	>72	>72	>72	>72	47	46	46
Ilife=720mA	Tc=25°C	>72	>72	>72	>72	>72	>72	>41	>41	>41
	Tc_nom=45°C	>72	>72	>72	>72	>72	>72	>41	>41	>41
	Tc_life=75°C	>72	>72	>72	>72	>72	>72	41	40	40

Lifetime

Parameter	Value	Unit
M70F50 nominal	>72000	hours
M70F50 life	>72000	hours

Performance Window




Wiring

Specification item	Value	Unit	Condition
Input wire cross-section	0.25...0.75	mm ²	solid wire
	18...24	AWG	solid wire
Input wire strip length	7.5...8.5	mm	
Input wire cross-section	0.33...0.5	mm ²	stranded wire
	20...22	AWG	stranded wire
Input wire strip length	7.5...8.5	mm	

Mechanical characteristics


Fortimo LED Strip 5ft MF 830 FC HV6
 Fortimo LED Strip 5ft MF 840 FC HV6
 Fortimo LED Strip 5ft MF 865 FC HV6

Parameter	Min	Typ	Max	Unit
Length	1398.2	1399.2	1400.2	mm
Width	19.8	20	20.6	mm
Height PCB	1.45	1.6	1.75	mm
Height Total		4.3		mm
Product mass		90.8		gram



Fortimo LED Strip 5ft MF 830 BC HV6
 Fortimo LED Strip 5ft MF 840 BC HV6

Parameter	Min	Typ	Max	Unit
Length	1398.2	1399.2	1400.2	mm
Width	19.8	20	20.6	mm
Height PCB	1.45	1.6	1.75	mm
Height Total		7.4		mm
Product mass		91		gram



Absolute ratings

Parameter	Min	Max	Unit
Current through the LED module (I-max)		720	mA
Case temperature (Tc-max)		85	°C
ESD (direct contact)	8		kV
Working voltage		350	V _{dc}

Application information

Certificates and Standards

CE
ENEC
ENEC+

Environmental

RoHS/REACH

Application

Dimming	Yes
---------	-----



© 2023 Signify Holding, IBRS 10461, 5600VB, NL. All rights reserved. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify.

www.philips.com/oem

Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V. All other trademarks are owned by Signify Holding or their respective owners.
UK importer address: Signify Commercial UK Limited, 3 Guildford Business Park, GU2 8XG

02/03/2023