

High Power 3535 Ceramic LED Mono-colour selector guide

- High intensity 3535 ceramic LED
- 3.5x3.5mm square
- Wide Angle
- Excellent thermal transfer



Applications

- Indoor Lighting
- Outdoor Lighting
- Industrial Lighting
- Architectural Lighting
- Consumer Lighting

Product Parameters

Color	Product Model	Benchmark	Power	Current/mA	Max Current/mA	CCT/Wavelength	Flux/lm@350mA
Red	RF-AL-C3535L2K1RE-02	XPG2-R1	3-5W	350	2000	620-625nm	70-90lm
	RF-AL-C3535L2K1RE-03	XPE2-R	3-5W	350	800	620-625nm	50-80lm
	RF-AL-C3535L2K1RE-04	XPG2-R	3-5W	350	1000	620-625nm	80-100lm
Green	RF-AL-C3535L2K1GR-03	XPE2-G	3-5W	350	1500	520-530nm	120-160lm
	RF-AL-C3535L2K1GR-04	XPG2-G	5-10W	350	2000	520-530nm	170-210lm
Blue	RF-AL-C3535L2K1RB-03	XPE2-B	3-5W	350	1500	465-475nm	30-50lm
	RF-AL-C3535L2K1RB-04	XPE2-B	3-5W	350	1500	450-460nm	20-40lm
	RF-AL-C3535L2K1RB-05	XPG2-B	3-5W	350	1500	465-475nm	30-50lm
Yellow	RF-AL-C3535L2K1YU-00	XPE2-Y	1-3W	350	750	585-595nm	40-60lm/100-120mW