

RF Mini Controller Selector Guide

The LTECH M series RF transmitters offer a choice 8 types, all of which are compatible with the M3-3A and M4-5A drivers to provide dimming, colour temperature control and RGB(W) colour mix. Available from UK stock for next-day delivery, the LTECH range offers high quality, great styling and competitive pricing. The LED controllers utilise advanced RF remote control, wireless signal with high output to achieve long transmission distances and reduce interference by obstacles.

LT-M1+M3-3A and M1+M4-5A LED Dimming Mini Controller

Colour wheel hand-held controller
M3-3A CV drive 3A/channel
M4-5A CV drive 5A/channel
Low voltage operation 12v ~ 24vdc
4096 grey scale for advanced control
Transmission distance 40~50 metres
RF Receiver drivers compatible with 6 different transmitters



LT-M2+M3-3A and M2+M4-5A 2-channel Colour Temperature Mini Controller

Colour wheel hand-held controller
M3-3A 2-channel CV drive 3A/channel
M4-5A 2-channel CV drive 5A/channel
Low voltage operation 12v ~ 24vdc
4096 grey scale for advanced control
Transmission distance 40~50 metres
Receiver driver compatible with 6 different transmitters



LT-M2+M3-3A and M2+M4-5A 3-channel Colour Temperature Mini Controller

Colour wheel hand-held controller
M3-3A 3-channel CV drive 3A/channel
M4-5A 3-channel CV drive 5A/channel
Low voltage operation 12v ~ 24vdc
4096 grey scale for advanced control
Transmission distance 40~50 metres
Receiver driver compatible with 6 different transmitters



LT-M3+M3-3A and M3+M4-5A 3-channel RGB Mini Controller

Colour wheel hand-held controller
M3-3A 3-channel CV drive 3A/channel
M4-5A 3-channel CV drive 5A/channel
Low voltage operation 5v ~ 24vdc
4096 grey scale for advanced control
Transmission distance 40~50 metres
Receiver driver compatible with 6 different transmitters



LT-M4+M4-3A and M4+M4-5A 4-channel RGBW Mini Controller

Colour wheel hand-held controller
M4-3A 4-channel CV drive 3A/channel
M4-5A 4-channel CV drive 5A/channel
Low voltage operation 5v ~ 24vdc
4096 grey scale for advanced control
Transmission distance 40~50 metres
Receiver driver compatible with 6 different transmitters



LT-M6+M4-3A and M4-5A 4-channel RGBW Mini Controller

Push button hand-held remote with additional functions
M4-3A 4-channel CV drive 3A/channel
M4-5A 4-channel CV drive 5A/channel
Low voltage operation 5v ~ 24vdc
4096 grey scale for advanced control
Transmission distance 40~50 metres
Receiver driver compatible with 6 different transmitters



LT-M8+M4-5A RGBW 4-channel Mini Controller

Push button hand-held remote with additional functions
M4-5A 4-channel CV drive 5A/channel
Low voltage operation 5v ~ 24vdc
4096 grey scale for advanced control
Transmission distance 40~50 metres
Receiver driver compatible with 6 different transmitters



LT-SPI16S+M16S SPI Pixel Addressable Mini Controller

Multi-channel pixel addressable LED transmitter & receiver designed to control each LED pixel in full colour RGB strips & fixtures

3-channel SPI control 10A
Low voltage operation 5v ~ 24vdc
Supports a range of IC types
Remote distance 40~50 metres

