


Refond 3535 High Power Infrared Emitter selector guide



Features includes

- Packaged Lens Design
- Low Profile
- Improved Illumination uniformity
- Upgraded Vision Coverage
- Enhanced peripheral image quality
- Directivity radiation 90 degrees

Applications

- CCTV & Security
- Face recognition



Part No.	IF(mA)	VF(V)	Ie(mW/sr)	λ P (nm)	P(mW)	$2\theta_{1/2}$ (°)	L*W*H(mm)
RF-E35A9-IRX-FR	500	1.4-2.0	/	830-870	280-350.	90	3.5 * 3.5 * 2.29
RF-E35A9-IRB-FR	1000	1.4-2.0	/	830-870	710-1120...	90	3.5 * 3.5 * 2.29
RF-E35S9-IRB-FR	1000	1.4-2.0	/	830-870	710-1120...	90	3.5 * 3.5 * 2.29
RF-E35Q9-IRB-FR	1000	1.4-2.0	/	830-870	710-1120...	90	3.5 * 3.5 * 2.29
RF-E35A9-IQD-FR	1000	1.4-2.0	/	930-970..	680-1120.	90	3.5 * 3.5 * 2.29
RF-E35A9-IPD-FR	1000	1.4-2.0	/	930-970	560-1120.	90	3.5 * 3.5 * 2.29
RF-E35A9-IRD-FR	1500	1.4-2.0	/	830-870	1200-1400.	90	3.5 * 3.5 * 2.29